

RV2017

20V Brushless Standard Type Open Tube Nut Runner



- Precise auto shut-off when it reaches the desired torque with LED and buzzer indicator of joint status for either good or not-good fixing
- The mechanical clutch technology enables precise and repeatable performance with minimal maintenance expenses
- Built-in 2-way wireless communication that can connect to a PLC unit or computer
- Improved ergonomics, weight, and reaction force with li-ion compact battery for fatigue-free working
- The brushless motor ensures the use of wear-free components, which reduces maintenance costs and extends the life cycle of the product



TECHNICAL SPECIFICATIONS

| Model | RV2017-WR12 | RV2017-WR20 | RV2017-WR27 |
|---------------------------|-------------------------------|-------------------------|----------------------|
| Voltage | 20V | | |
| Hex Size | 7,8,9,10,11,12,13,14,15,16 mm | 17,18,19,20,21,22,23 mm | 24,25,27,29,30,32 mm |
| Torque Range | 3 - 12 Nm | 6 - 20 Nm | 8 - 27 Nm |
| Programmable Speed | 525 - 750 RPM | 350 - 500 RPM | 262 - 375 RPM |
| Length (w/o battery) | 53.9 cm | 56.3 cm | 58.7 cm |
| Tool Weight (w/o battery) | 1.95 kg | 2.09 kg | 2.32 kg |

TECHNOLOGIES



DC motors have traditionally been driven by carbon brushes to power the motor. Over time these wear out and need replacing. All our motors are brushless meaning that the motor is controlled electronically without the need for carbon brushes ensuring your tool is maintenance-free.



We have leveraged decades of electrical expertise from some of the world's leading electrical engineers to develop our wireless platform to record and control our professional assembly tools, that can be remotely controlled via our software or different protocols for PLC systems.



Our patent-pending All-In-One motor includes the power, control & communication board along with the automatic winding stator with an interior permanent magnet design rotor, all enclosed in a die-cast cover. These one-unit components have several advantages, including weight reduction, longer lifespan, and crucially our number one design goal of efficiency as there are no additional components to cool.

TOOL FEATURES



The mechanical clutch prevents over-tightening of fasteners by disengaging the drive mechanism when a preset torque level is reached, ensuring precision and preventing damage.



The auto shut-off function automatically shuts down the tool to prevent over-tightening and enhance safety during operation.



Low vibration minimises the risk of injury and fatigue on the operator, making it safer to use for long periods.




Our buzzer serves as an audible alert to notify the user of specific conditions or errors during operation, enhancing safety and efficiency.



Illuminate your workspace with the built-in LED light on this power tool, ensuring visibility in low-light conditions for enhanced work safety.

DIMENSIONAL DRAWING



HEAD DIMENSION SPECIFICATIONS

| Product Number | A | B | C | D | E | F | G | K |
|----------------|---------|-------|-------|---------|---------|-------|----------|----------------|
| RV2017-WR12 | 46.2 mm | 14 mm | 18 mm | 13.6 mm | 31 mm | 40 mm | 58.8 mm | 5 - 10.9 mm |
| RV2017-WR20 | 57.2 mm | 14 mm | 18 mm | 20.6 mm | 46.6 mm | 48 mm | 83.2 mm | 11.3 - 15.5 mm |
| RV2017-WR27 | 71 mm | 14 mm | 18 mm | 26.6 mm | 59 mm | 59 mm | 106.6 mm | 16.1 - 21.2 mm |