

## RZ6008

### 60V Concrete Vibrator



- High-speed, low-impact vibration ensures effective concrete consolidation without damaging the surface of the ICF
- High efficiency: max no load vibration at up to 13,000 per minute, with up to 200 mins continuous run-time
- Interchangeable attachments for various applications
- Battery pack protective cover and trigger lock
- Perfect for a slabs, steps, and other concrete applications



### TECHNICAL SPECIFICATIONS



Option	RZ6008-KCA	RZ6008-25DS	RZ6008-28DL	RZ6008-28FP	RZ6008-28FPL
Type	Wall	Rigid	Rigid	Flexible	Flexible
Voltage	60V				
Vibrations per Minute	9,500 VPM	13,000 VPM	12,500 VPM	12,500 VPM	13,000 VPM
Max. Run-time (2.0Ah Battery)	130 mins	120 mins	100 mins	200 mins	130 mins
Head Dimension (Ø x Length)	Ø 76 mm x 133 mm	Ø 25 x 447 mm	Ø 28 x 635 mm	Ø 28 x 186 mm	Ø 28 x 186 mm
Total Length (w/o battery)	410 mm	748 mm	936 mm	1070 mm	1474 mm
Tool Weight (w/o battery)	3.08 kg	3.28 kg	4.18 kg	2.98 kg	3.98 kg

### TOOL FEATURES



Experience effortless manoeuvrability and reduced fatigue with this lightweight design, ideal for extended use on various projects.



The compact design philosophy to prioritise ensures easy handling and maneuverability in tight spaces, without compromising on performance or power.



The low vibration properties of oil pulse tools minimize user fatigue and increase precision by damping the impact force through a fluid-driven mechanism.