

RM325-2I

Interchangeable Digital Torque Wrench



- Audible torque confirmation using a buzzer, LED flashing & vibration function
- Standard functions: torque setting, measurement setting, mode setting
- Operation in both clockwise and counter-clockwise directions
- LCD display shows kg-cm, N-m, in-lb, ft-lb, 0.1° measurements
- Easy to set up Peak or Trace modes
- Anti-slip soft grip



TECHNICAL SPECIFICATIONS

Drive	1/4" Square
Voltage	3 Vdc
Head Type	Quick Release Ratchet
Length	403 mm
Accuracy	CW: ± 1.5% CCW: ±2.5%
Accuracy Angle	+/-2°
Operating Torque Range	17 - 340 Nm
Operating Angle Range	720°
Memory Capacity	30 data sheets
LED	2 LED (Green and Red)
Vibration Warning	Yes (While reaching to 90% of setting value)
Resolution	1 kg-cm / 0.1 Nm / 1 in-lb / 0.1 ft-lb / 1°
Operation Mode	Peak (K) / Trace (F) / Angle (A)
Power Saving Mode	After 3 Minutes of no use
Operating Temperature	-10°C ~ 60°C
Storage Temperature	-20°C ~ 70°C
Battery	AA (Alkaline) Battery x2
Weight (w/o battery)	0.75 kg

TECHNOLOGIES



Utilizing the next generation of electrical technology, we can detect the angle of the head to calculate how many turns the anvil has rotated. For Digital Torque products this is accurate to 1%.

TOOL FEATURES



Built-in angle function with accuracy $\pm 2\%$ with 1° increments.



The LED flashing feature on this power tool signals important alerts and warnings, enhancing safety and efficiency during operation.



Required AA Batteries



Our buzzer serves as an audible alert to notify the user of specific conditions or errors during operation, enhancing safety and efficiency



Vibration feedback to the user once 90% of the target torque is reached.