

## RM327-3I

### Interchangeable Digital Torque Wrenche



- Audible torque confirmation using a buzzer, LED flashing & vibration function
- Standard functions: torque setting, measurement setting, mode setting
- Operation in both clockwise and counter-clockwise directions
- LCD display shows kg-cm, N-m, in-lb, ft-lb, 0.1° measurements
- Easy to set up Peak or Trace modes
- Anti-slip soft grip



### TECHNICAL SPECIFICATIONS

Drive	3/8" Square
Voltage	3 Vdc
Head Type	Interchangeable (For 9 x 12 mm insert)
Length	425 mm
Accuracy	CW: ± 2%    CCW: ± 3%
Operating Torque Range	13.5 - 135 Nm
Memory Capacity	30 data sets
LED	2 LED (Green and Red)
Vibration Warning	Yes (While reaching to 90% of setting value)
Resolution	1 kg-cm / 0.1 Nm / 1 in-lb / 0.1 ft-lb
Operation Mode	Peak (K) / Trace (F)
Power Saving Mode	After 2 Minutes of no use
Operating Temperature	-10°C ~ 60°C
Storage Temperature	-20°C ~ 70°C
Battery	AA (Alkaline) Battery x2
Weight (w/o battery)	0.90 kg

### TOOL FEATURES



Interchangeable head, ideal for tight access



Our buzzer serves as an audible alert to notify the user of specific conditions or errors during operation, enhancing safety and efficiency

# DUROFIX™



The LED flashing feature on this power tool signals important alerts and warnings, enhancing safety and efficiency during operation.



Vibration feedback to the user once 90% of the target torque is reached.



Required AA Batteries