

RM602-3

Digital Torque Adapters



- Static torque measurement
- Standard functions: torque setting, measurement setting and mode setting
- Operation in both clockwise and counter-clockwise directions
- Back-lit LCD display shows Nm, kg-cm, in-lb, ft-lb measurements
- Audible torque confirmation by means of buzzer
- Easy to Set, Peak, or Trace modes



TECHNICAL SPECIFICATIONS

Drive	3/8" Square
Voltage	6Vdc
Length	75 mm
Width	47 mm
Height	48 mm
Accuracy	CW: ± 2% CCW: ±3%
Accuracy Angle	+/-2°
Operating Range	80 Nm
Setting Range	8 - 80 Nm
Memory Capacity	30 data sheets
Resolution	1 kg-cm / 0.1 Nm / 1 in-lb / 0.1 ft-lb
Operation Mode	Peak (K) / Trace (F)
Resolution	1 kg-cm / 0.1 Nm / 1 in-lb / 0.1 ft-lb / 1°
Operation Mode	Peak (K) / Trace (F) / Angle (A)
Power Saving Mode	After 3 Minutes of no use
Operating Temperature	0°C ~ 50°C
Storage Temperature	-10°C ~ 60°C
Battery	AA (Alkaline) Battery x2
Weight (w/o battery)	0.14 kg

TOOL FEATURES



Requires a coin cell battery.



Our buzzer serves as an audible alert to notify the user of specific conditions or errors during operation, enhancing safety and efficiency



The LED flashing feature on this power tool signals important alerts and warnings, enhancing safety and efficiency during operation.