RM602-4

Digital Torque Adapters

- Static torque measurement
- Standard functions: torque setting, measurement setting and mode setting
- Operation in both clockwise and counter-clockwise directions
- Back-lit LCD display shows Nm, kg-cm, in-lb, ft-lb measurements
- Audible torque confirmation by means of buzzer
- Easy to Set, Peak, or Trace modes

TECHNICAL SPECIFICATIONS

Drive	1/2" Square
Voltage	6Vdc
Length	75 mm
Width	47 mm
Height	48 mm
Accuracy	CW: ± 2% CCW: ±3%
Operating Range	340 Nm
Setting Range	34 - 340 Nm
Memory Capacity	30 data sheets
Resolution	1 kg-cm / 0.1 Nm / 1 in-lb / 0.1 ft-lb
Operation Mode	Peak *(K)* / Trace *(F)*
Resolution	1 kg-cm / 0.1 Nm / 1 in-lb / 0.1 ft-lb / 1°
Operation Mode	Peak *(K)* / Trace *(F)* / Angle *(A)*
Power Saving Mode	After 3 Minutes of no use
Operating Temperature	0°C ~ 50°C
Storage Temperature	-10°C ~ 60°C
Battery	Coin Cell *(CR2032)* Battery x1
Weight (w/o battery)	0.20 kg

Durofix may change specifications at any time due to ongoing policy improvements. Details correct as of 10/04/2024

TOOL FEATURES

COIN CELL REQUIRED

Requires a coin cell battery.

LED FLASHING

The LED flashing feature on this power tool signals important alerts and warnings, enhancing safety and efficiency during operation.

BUZZER

Our buzzer serves as an audible alert to notify the user of specific conditions or errors during operation, enhancing safety and efficiency