

RM602-4

Digital Torque Adapters



- Static torque measurement
- Standard functions: torque setting, measurement setting and mode setting
- Operation in both clockwise and counter-clockwise directions
- Back-lit LCD display shows Nm, kg-cm, in-lb, ft-lb measurements
- Audible torque confirmation by means of buzzer
- Easy to Set, Peak, or Trace modes



TECHNICAL SPECIFICATIONS

| | |
|-----------------------|---|
| Drive | 1/2" Square |
| Voltage | 6Vdc |
| Length | 75 mm |
| Width | 47 mm |
| Height | 48 mm |
| Accuracy | CW: ± 2% CCW: ± 3% |
| Accuracy Angle | +/- 2° |
| Operating Range | 340 Nm |
| Setting Range | 34 - 340 Nm |
| Memory Capacity | 30 data sheets |
| Resolution | 1 kg-cm / 0.1 Nm / 1 in-lb / 0.1 ft-lb |
| Operation Mode | Peak (K) / Trace (F) |
| Resolution | 1 kg-cm / 0.1 Nm / 1 in-lb / 0.1 ft-lb / 1° |
| Operation Mode | Peak (K) / Trace (F) / Angle (A) |
| Power Saving Mode | After 3 Minutes of no use |
| Operating Temperature | 0°C ~ 50°C |
| Storage Temperature | -10°C ~ 60°C |
| Battery | AA (Alkaline) Battery x2 |
| Weight (w/o battery) | 0.20 kg |

TOOL FEATURES



Requires a coin cell battery.



Our buzzer serves as an audible alert to notify the user of specific conditions or errors during operation, enhancing safety and efficiency



The LED flashing feature on this power tool signals important alerts and warnings, enhancing safety and efficiency during operation.